

Eliminator

Bio-Green Formula

PRODUCT DATA SHEET

Eliminator Bio Green is an innovative powerful, allpurpose, water-based cleaner that is fit for the toughest industrial needs.



Eliminator Bio Green is a proprietary blend of Class 1, ATCC certified microbes; Eliminator Bio Green will assist in converting oils, greases, and fat removed during the cleaning process to safer carbon dioxide and water effluent. This earth friendly, bio-compatible cleaner is ideal for enhancing the efficiency of any system that currently utilizes a microbial treatment.

Eliminator Bio Green is strong enough to remove substances ranging from general industrial cleaning to heavier greases and oils. As it is readily bio-degradable, it contains no Butyl, Phosphates, Nitrates, Chlorinated Solvents, or Petroleum by-products. Eliminator Bio Green meets the California South Coast Air Quality Management District cleaner specifications by containing less than 50 g/l VOC in dilution.

Eliminator Bio Green requires no additional handling or storing precautions. It is safe to store in normal settings and is both user and eco friendly.

Eliminator Bio Green is an amazing product that will not only reduce your carbon footprint, but also meets all the standards that are considered to be an environmentally conscious cleaner.



Size	Part #	Pack
1 gallon	81001	192/plt
5 gallon	81005	48/plt
55 gallon	81055	4/plt



**ELIMINATOR BIO GREEN CLEANER PLUS CLEANER CONCENTRATE IS:
A Low-VOC, water-base degreaser with a powerful microbial package added for the toughest industrial needs.**

Benefits:

- ▶ Non-toxic
- ▶ No corrosive enhancers (as common in most heavy-duty degreasers)
- ▶ No petro-chemicals
- ▶ ATCC Bacterial Package for Complete Degreasing
- ▶ Readily Bio-Degradable
- ▶ Compatible with oil water separators

Features:

- ▶ Contains no phosphates, nitrates, sulphates, caustics, terpenes, chlorinated solvents or petroleum by-products.
- ▶ Less than 50g/l VOC in dilution as tested by SCAQMD
- ▶ pH 9-9.5 in concentrate form

Oil Sponge UC+ can be used in:

- ▶ Mop Buckets
- ▶ Parts Washers
- ▶ Power Sprayers
- ▶ Soak Tanks
- ▶ Spray Bottles
- ▶ Wipe Applications

Oil Sponge UC+ is needed in the following areas:

- ▶ Automotive Mfg. & Repair (Interior-to-Exterior-to-Engine Degreasing)
- ▶ Bars, Bistros, & Restaurants
- ▶ Hospitals & Other Institutions
- ▶ Hotels & Motels
- ▶ Household
- ▶ Machine Shops
- ▶ Military
- ▶ Shipyards & Marinas (Bilges-to-Decks)

Oil Sponge UC+ can be stored in general chemical bays kept between 32° to 120°f.

Dilution Guidelines: Type, age and build-up of soils will determine dilution concentration and need to be determined on-site through simple application testing.

Heavy-Duty: 1:0 to 1:3

Medium-Duty: 1:4 to 1:10

Light-Duty: 1:11 to 1:32

Physical Characteristics:

Appearance: Green Colored Liquid

Odor: Negligible

Specific Gravity: 1.02

Vapor Density: (Air=1) >1

pH: 9-10

Solubility in water: 100%

Percent Volatile: >89%

Freezing Point: ca 32° f

VOC: <10g/L

Directions for use: Dilute solution to proper ratio; apply by spray or wipe method. Some mechanical motion may be required to assist in the agitation of the soils. Rinse clean; repeat if necessary.

MANUFACTURED BY:

PHASE III



Chandler, AZ 85225
480.503.2847 p
480.503.1077 f
www.phaseiii.com
www.oilsponge.com

DISTRIBUTED BY: